



Reibgeschweisste Bohrgestänge API

Abmessungen

A	FIL	C	H	E	F	G
76,1	2"3/8 API Reg	30	65	40	14	90
88,9	2"3/8 API Reg	30	75	40	22	98
	2"3/8 API IF	40	75	40	22	98
	2"7/8 API Reg	30	75	40	17	106
95	Nordmeyer	58	80	40	15	90
101,6	2"7/8 API Reg	30	85	40	18	113
	2"7/8 API IF	50	85	40	24	113
114,3	2"7/8 API IF	50	90	50	14	103
	3"1/2 API Reg	40	90	50	18	103
	3"1/2 API IF	65	90	40	28	130
127	3"1/2 API Reg	40	105	40	14	109
	3"1/2 API IF	65	105	40	18	120
139,7	4"1/2 API Reg	60	120	40	18	126
	3"1/2 API Reg	40	120	40	31	126
	3"1/2 API IF	65	120	40	21	126
	4" IF	80	120	40	25	140
152,4	4" IF	80	130	50	25	140
	4"1/2 API Reg	60	130	50	32	138
	4"1/2 API IF	89	130	50	25	138
168,3	4"1/2 API Reg	60	145	50	30	138
	4"1/2 API IF	89	145	50	23	138
177,8	6"5/8 API Reg	100	160	50	31	158
	4"1/2 API IF	89	160	50	43	158
193,7	6"5/8 API Reg	100	170	50	31	158
	4"1/2 API IF	60	170	50	30	138
203	6"5/8 API Reg	100	180	50	31	132
	7"5/8 API Reg	110	180	50	31	130
219,1	6"5/8 API Reg	100	190	50	30	157
	7"5/8 API Reg	110	190	50	31	164
	8"5/8 API Reg	110	190	50	30	167