



BOHRGESTÄNGE reibgeschweisst API REG.

Durchmesser mm	Grösse in Zoll	Nutzlänge mm	WS mm	Gewicht Kg
76.1	2"3/8 API Reg	1000	6.3	15.1
76.1		1500	6.3	20.5
76.1		2000	6.3	25.9
76.1		3000	6.3	36.8
88.9	2"3/8 API Reg	1000	6.3	18.7
88.9		1500	6.3	25.2
88.9		2000	6.3	31.7
88.9		3000	6.3	44.5
95	Nordmeyer	1000	6.3	21.9
95	Konisch	1500	6.3	28.3
95	Trapez.	2000	6.3	34.8
95	4G1"	3000	6.3	47.8
114.3	3"1/2 API Reg	1000	6.3	28.3
114.3		1500	6.3	37.0
114.3		2000	6.3	45.4
114.3		3000	6.3	62.2
127	3"1/2 API Reg	1000	6.3	32.3
127		1500	6.3	41.6
127		2000	6.3	50.9
127		3000	6.3	69.7
139.7	4"1/2 API Reg	1000	6.3	38.6
139.7		1500	6.3	49.0
139.7		2000	6.3	59.4
139.7		3000	6.3	80.1
152.4	4"1/2 API Reg	1000	6.3	73.0
152.4		1500	6.3	84.0
152.4		2000	6.3	95.0
152.4		3000	6.3	118.0



BOHRGESTÄNGE reibgeschweisst API REG.

Durchmesser mm	Grösse in Zoll	Nutzlänge mm	WS mm	Gewicht Kg
168.3	4"1/2 API Reg	1000	8.8	92.0
168.3		1500	8.8	107.0
168.3		2000	8.8	140.0
168.3		3000	8.8	188.0
177.8	6"5/8 API Reg	1000	8.8	81.0
177.8		1500	8.8	98.0
177.8		2000	8.8	115.0
177.8		3000	8.8	150.0
193.7	4"1/2-6"5/8 API Reg	1000	8.8	100.0
193.7		1500	8.8	125.0
193.7		2000	8.8	150.0
193.7		3000	8.8	180.0
219.1	6"5/8-7"5/8 API Reg und 8"5/8 API Reg	1000	8.8	104.0
219.1		1500	8.8	132.0
219.1		2000	8.8	160.0
219.1		3000	8.8	195.0

Alle Bohrgestänge sind Lieferbar in Wandstärke 8 mm bis 88,9 und 8,8 mm bis 152,4 mm

BOHRGESTÄNGE reibgeschweisst Spezialausführung

Durchmesser mm	Wandstärke	Gewinde
42	6.3	
54	6.3	R 45
60	6.3	R 45/CR
70	4.0	506 RF/47HL