

## Bohrgestänge reibgeschweisst API IF

Durchmesser mm	Grösse in Zoll	Nutzlänge mm	WS mm	Gewicht kg
88.9	2"3/8 API IF	1000	6.3	18.7
88.9		1500	6.3	25.2
88.9		2000	6.3	31.7
88.9		3000	6.3	44.5
114.3	3"1/2 API IF	1000	6.3	28.3
114.3		1500	6.3	37.0
114.3		2000	6.3	45.4
114.3		3000	6.3	62.2
127	3"1/2 API IF	1000	6.3	32.3
127		1500	6.3	41.6
127		2000	6.3	50.9
127		3000	6.3	69.7
139.7	3"1/2 +4"1/2 API IF	1000	6.3	38.6
139.7		1500	6.3	49.0
139.7		2000	6.3	59.4
139.7		3000	6.3	80.1
152.4	4"1/2 API IF	1000	6.3	73.0
152.4		1500	6.3	84.0
152.4		2000	6.3	95.0
152.4		3000	6.3	118.0
168.3	4"1/2 API IF	1000	8.8	92.0
168.3		1500	8.8	107.0
168.3		2000	8.8	140.0
168.3		3000	8.8	188.0
168.3	4"1/2 API IF	1000	8.8	92.0
168.3		1500	8.8	107.0
168.3		2000	8.8	140.0
168.3		3000	8.8	188.0
177.8	4"1/2 API IF	1000	8.8	81.0
177.8	6"5/8 API Reg	1500	8.8	98.0
177.8		2000	8.8	115.0
177.8		3000	8.8	150.0

*Alle Bohrgestänge sind Lieferbar in Wandstärke 8 mm bis 88,9 und 8,8 mm bis 152,4 mm*