

# Futterrohre

Schaftrohr aus Stahl  $F_y \geq 552 \text{ N/mm}^2$   
Doppelzapfen aus Stahl 42CrMo4V



## Futterrohre

Durchmesser mm	Nutzlänge mm	WS mm	Innen Ø mm	Gewicht kg
101,6	1000	8.8	82	20,0
101,6	1500	8.8	82	30,0
101,6	2000	8.8	82	40,0
101,6	3000	8.8	82	60,0
114.3	1000	8.8	94	24,0
114.3	1500	8.8	94	35,0
114.3	2000	8.8	94	48,0
114.3	3000	8.8	94	69,0
127	1000	8.8	107	26,0
127	1500	8.8	107	39,0
127	2000	8.8	107	52,0
127	3000	8.8	107	77,0
133	1000	8.8	113	28,0
133	1500	8.8	113	41,0
133	2000	8.8	113	56,0
133	3000	8.8	113	84,0
139.7	1000	8.8	120	30,0
139.7	1500	8.8	120	44,0
139.7	2000	8.8	120	60,0
139.7	3000	8.8	120	86,0
152.4	1000	8.8	133	31,5
152.4	1500	8.8	133	47,0
152.4	2000	8.8	133	63,0
152.4	3000	8.8	133	94,0
168.3	1000	8.8	147	36,0
168.3	1500	8.8	147	53,0
168.3	2000	8.8	147	72,0
168.3	3000	8.8	147	105,0
177.8	1000	8.8	158	38,0
177.8	1500	8.8	158	56,0
177.8	2000	8.8	158	76,0
177.8	3000	8.8	158	110,0

## Futterrohre

Durchmesser mm	Nutzlänge mm	WS mm	Innen Ø mm	Gewicht kg
193.7	1000	8.8	171	41.0
193.7	1500	8.8	171	61.0
193.7	2000	8.8	171	82.0
193.7	3000	8.8	171	121.0
203	1000	8.8	178	44.0
203	1500	8.8	178	65.0
203	2000	8.8	178	88.0
203	1500	8.8	178	65.0
203	2000	8.8	178	88.0
203	3000	8.8	178	128.0
219.1	1000	8.8	197	47.0
219.1	1500	8.8	197	70.0
219.1	2000	8.8	197	94.0
219.1	3000	8.8	197	138.0
244.5	1000	10.0	222	58.0
244.5	1500	10.0	222	67.0
244.5	2000	10.0	222	116.0
244.5	3000	10.0	222	174.0
273	1000	10.0	248	65.0
273	1500	10.0	248	97.0
273	2000	10.0	248	130.0
273	3000	10.0	248	195.0
298.5	1000	10.0	275	73.0
298.5	1500	10.0	275	109.0
298.5	2000	10.0	275	146.0
298.5	3000	10.0	275	216.0
323.9	1000	12.5	298	100.0
323.9	1500	12.5	298	150.0
323.9	2000	12.5	298	200.0
323.9	3000	12.5	298	300.0
355.6	1000	12.5	329	115.0
355.6	1500	12.5	329	172.5
355.6	2000	12.5	329	230.0
355.6	3000	12.5	329	287.5

## Futterrohre

Durchmesser mm	Nutzlänge mm	WS mm	Innen Ø mm	Gewicht kg
368	1000	12.5	343	118.0
368	1500	12.5	343	173.0
368	2000	12.5	343	228.0
368	3000	12.5	343	338.0
406.4	1000	12.5	380	130.0
406.4	1500	12.5	380	195.0
406.4	2000	12.5	380	260.0
406.4	3000	12.5	380	390.0
457,2	1000	12,5	430	148,0
457,2	1500	12,5	430	217,0
457,2	2000	12,5	430	287,0
457,2	3000	12,5	430	427,0
473.1	1000	12,5-13.5	446	154.0
473.1	1500	12,5-13.5	446	221.0
473.1	2000	12,5-13.5	446	291.0
473.1	3000	12,5-13.5	446	431.0
508	1000	12.5	480	163.0
508	1500	12.5	480	240.0
508	2000	12,5	480	320.0
508	3000	12,5	480	472.0
609,6	1000	14,2	575	220.0
609,6	1500	14,2	575	326.0
609,6	2000	14,2	575	430,0